



### ➤ General Description

This PAN00TP26P N-Channel enhancement mode power field effect transistor is the high density technology and this advanced technology can provide excellent Rds(On) performance and efficiency for power switching and load switching application., this device also comply with the RoHS and Green Product requirement with full function reliability approved.

### ➤ Feature

- Super Low Gate Charge
- Green Device Available Excellent
- Cdv/dt effect decline
- Advanced high cell densit Trench
- TO-263-2L package design

### ➤ TO-263-2L



### ➤ Application

- DC-DC Converters
- Power Management
- Analog Switch

### ➤ Absolute Maximum Ratings

Parameter	Symbol	Rating	Units
Drain-Source Voltage	$V_{DS}$	100	V
Gate-Source Voltage	$V_{GS}$	$\pm 20$	V
Continuous Drain Current, $V_{GS}$ @ 10V <sub>1</sub>	$I_D@T_C=25^\circ C$	40	A
Continuous Drain Current, $V_{GS}$ @ 10V <sub>1</sub>	$I_D@T_C=70^\circ C$	22	A
Pulsed Drain Current <sub>2</sub>	$I_{DM}$	75	A
Single Pulse Avalanche Energy <sub>3</sub>	EAS	16	mJ
Avalanche Current	$I_{AS}$	18	A
Total Power Dissipation <sub>4</sub>	$P_D@T_C=25^\circ C$	62.5	W
Storage Temperature Range	$T_{STG}$	-55 to 150	$^\circ C$
Operating Junction Temperature Range	$T_J$	-55 to 150	$^\circ C$
Thermal Resistance Junction-Ambient <sub>1</sub>	$R_{\theta JA}$	50	$^\circ C/W$
Thermal Resistance Junction-Case <sub>1</sub>	$R_{\theta JC}$	2	$^\circ C/W$

### ➤ Electrical Characteristics ( $T_J=25^\circ C$ Unless otherwise noted)

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
Drain-Source Breakdown Voltage	$BV_{DSS}$	$V_{GS}=0V$ , $I_D=250\mu A$	100	---	---	V
Static Drain-Source On-Resistance <sup>2</sup>	$R_{DS(ON)}$	$V_{GS}=10V$ , $I_D=9A$	---	16	22	m $\Omega$
		$V_{GS}=4.5V$ , $I_D=7A$	---	20	28	
Gate Threshold Voltage	$V_{GS(th)}$	$V_{GS}=V_{DS}$ , $I_D=250\mu A$	1.2	---	2.5	V
Drain-Source Leakage Current	$I_{DSS}$	$V_{DS}=80V$ , $V_{GS}=0V$ , $T_J=25^\circ C$	---	---	1	uA
		$V_{DS}=80V$ , $V_{GS}=0V$ , $T_J=55^\circ C$	---	---	100	
Gate-Source Leakage Current	$I_{GSS}$	$V_{GS}=\pm 20V$ , $V_{DS}=0V$	---	---	$\pm 100$	nA
Forward Transconductance	$g_{fs}$	$V_{DS}=5V$ , $I_D=9A$	---	28	---	S
Gate Resistance	$R_g$	$V_{DS}=0V$ , $V_{GS}=0V$ , $f=1MHz$	---	1.6	---	$\Omega$
Total Gate Charge (10V)	$Q_g$	$V_{DS}=80V$ , $V_{GS}=10V$ , $I_D=7A$	---	36	---	nC
Gate-Source Charge	$Q_{gs}$		---	5	---	
Gate-Drain Charge	$Q_{gd}$		---	10	---	
Turn-On Delay Time	$T_{d(on)}$	$V_{DD}=50V$ , $V_{GS}=10V$ , $R_G=3.3\Omega$ , $I_D=7A$	---	11.5	---	ns
Rise Time	$T_r$		---	29	---	
Turn-Off Delay Time	$T_{d(off)}$		---	42	---	
Fall Time	$T_f$		---	18	---	
Input Capacitance	$C_{iss}$	$V_{DS}=15V$ , $V_{GS}=0V$ , $f=1MHz$	---	1930	---	pF
Output Capacitance	$C_{oss}$		---	245	---	
Reverse Transfer Capacitance	$C_{rss}$		---	125	---	


### ➤ Diode Characteristics

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
Continuous Source Current <sup>1,6</sup>	$I_S$	$V_G=V_D=0V$ , Force Current	---	---	40	A
Pulsed Source Current <sup>2,6</sup>	$I_{SM}$		---	---	75	A
Diode Forward Voltage <sup>2</sup>	$V_{SD}$	$V_{GS}=0V$ , $I_S=1A$ , $T_J=25^\circ C$	---	---	1.2	V
Reverse Recovery Time	$t_{rr}$	$I_F=7A$ , $di/dt=100A/\mu s$ , $T_J=25^\circ C$	---	48	---	nS
Reverse Recovery Charge	$Q_{rr}$		---	29	---	nC


Note :

- 1.Pulse width limited by maximum junction temperature.
- 2.The data tested by pulsed , pulse width  $\leq 300\mu s$  , duty cycle  $\leq 2\%$
- 3.The EAS data shows Max. rating . The test condition is  $V_{DD}=25V$ ,  $V_{GS}=10V$ ,  $L=0.1mH$
- 4.Ensure that the channel temperature does not exceed  $150^\circ C$ .
- 5.The data is theoretically the same as  $I_D$  and  $I_{DM}$  , in real applications , should be limited by total power dissipation.


### ➤ Typical Characteristics




**Fig.1 Typical Output Characteristics**




**Fig.2 On-Resistance vs. Gate-Source Voltage**




**Fig.3 Forward Characteristics of Reverse**




**Fig.4 Gate-Charge Characteristics**




**Fig.5 Normalized  $V_{GS(th)}$  vs.  $T_J$**




**Fig.6 Normalized  $R_{DS(on)}$  vs.  $T_J$**




**Fig.7 Capacitance**




**Fig.8 Safe Operating Area**



**Fig.9 Normalized Maximum Transient Thermal Impedance**




**Fig.10 Switching Time Waveform**



**Fig.11 Unclamped Inductive Switching Waveform**

## ➤ Recommend IR Reflow Soldering Thermal Profile




Profile Feature	Pb-Free Assembly Profile
Temperature Min. (T <sub>smin</sub> )	150°C
Temperature Max. (T <sub>smax</sub> )	200°C
Time (t <sub>s</sub> ) from (T <sub>smin</sub> to T <sub>smax</sub> )	60-120 seconds
Average Ramp-up Rate (t <sub>L</sub> to t <sub>P</sub> )	3°C/second max.
Liquidous Temperature (T <sub>L</sub> )	217°C
Time (t <sub>L</sub> ) Maintained Above (T <sub>L</sub> )	60 – 150 seconds
Peak Temperature	260°C +0°C / -5°C
Time (t <sub>P</sub> ) within 5°C of actual Peak Temperature	30 seconds
Ramp-down Rate (T <sub>P</sub> to T <sub>L</sub> )	6°C/second max
Time 25°C to Peak Temperature	8 minutes max.

## ➤ Ordering Information

Part Number	Description	Quantity
PAN00TP26P	TO-263-2L Reel	800

### ➤ Package Information ( TO-263-2L )



SYMBOLS	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	4.370	4.770	0.172	0.188
A1	1.220	1.420	0.048	0.056
A2	2.200	2.890	0.087	0.114
A3	0.000	0.250	0.000	0.010
b	0.700	0.960	0.028	0.038
b1	1.170	1.470	0.046	0.058
c	0.300	0.530	0.012	0.021
D1	8.500	9.300	0.335	0.366
D4	6.600	-	0.260	-
E	9.860	10.36	0.388	0.408
E5	7.060	-	0.278	-
e	2.540 BSC		0.100 BSC	
H	14.70	15.70	0.579	0.618
H2	1.070	1.470	0.042	0.058
L	2.000	2.600	0.079	0.102
L1	1.400	1.750	0.055	0.069
L4	0.250 BSC		0.010 BSC	
θ	0°	9°	0°	9°

otice.

## DISCLAIMER

- The information in this document and any product described herein are subject to change without notice and should not be construed as a commitment by Paceleader, Paceleader reserve the right to make changes to the information in this document.
- Though Paceleader make effort to improve product quality and reliability, Product can malfunction and fail due to their inherent electrical sensitivity and vulnerability to physical stress, it is the responsibility of the customer, when utilizing Paceleader products, to comply with the standards of safety in making a safe design for entire system and to avoid situation in which a malfunction or failure., In developing a new designs, customer should ensure that the device which shown in this documents are used within specified operatingranges.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by Paceleader for any infringements of patents or other rights of the third parties which may result from its use.